

March 1965


Brief 65-10044

# NASA TECH BRIEF



NASA Tech Briefs are issued by the Technology Utilization Division to summarize specific technical innovations derived from the space program. Copies are available to the public from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia, 22151.

## Flexible Curtain Shields Equipment from Intense Heat Fluxes



CURTAIN CROSS-SECTION

**The problem:** Shielding equipment from intense heat fluxes radiated by the exhaust from large rocket engines undergoing tests at proving grounds. A flexible, high strength curtain capable of providing protection against heat fluxes of up to 40 Btu/sq ft/sec for approximately 2-minute intervals was required.

**The solution:** A curtain made of fiberglass-silicone elastomer laminate.

**How it's done:** Panels of greige-grade, two-ply silicone-calendered (imbedded) fiberglass fabric are coated with silicone primer, followed by coating with a silicone elastomer compound plus catalyst. The panels are then treated in an oven at approximately 350°F to cure the elastomer. The panels are sewn together with fiberglass thread. The curtain is next covered with a 0.025-inch blanket of a commercially available fibrous silica and finally with an outer wrapping of 0.007-inch adhesive-backed aluminum foil. Metal snap fasteners are used to keep the curtain in place.

The curtain is strong, flexible, peel-resistant, wrinkle-free, lightweight, and only about 0.25 inch thick.

### Notes:

1. Applications of this curtain are suggested for thermal shielding in areas which need not be permanently enclosed by bulkier walls.
2. Inquiries concerning this innovation may be directed to:

Technology Utilization Officer  
Marshall Space Flight Center  
Huntsville, Alabama, 35812  
Reference: B65-10044

**Patent status:** NASA encourages commercial use of this innovation. No patent action is contemplated.

Source: Arrowhead Products under contract to Marshall Space Flight Center (M-FS-48)

Category No. 03